

Carpet Adhesive

3095

○ SUPERIOR



Roberts® 3095 a superior, high-performing commercial-grade carpet adhesive developed for the most demanding carpet installations. Roberts 3095 is an excellent adhesive for double-bond installations.

Features:

- Moisture Control Adhesive – up to 10lbs MVER (ASTM F1869) / 90%RH (ASTM F2170)
- High solids, high tack formulation
- Extremely fast grabbing adhesive to hold down the most rigid backings
- Excellent for direct and double bond installation methods
- Enviro-Friendly - solvent-free and LEED® compliant; VOC <1g/L, SCAQMD Rule 1168
- Non-flammable. NFPA Class A and UBC Class 1 fire resistance ratings (ASTM E84)
- CRI Green Label Plus Certified – GPL #36471
- GoldGuard® antimicrobial product protection
- Traffic – heavy commercial

Uses:

For adhering most commercial carpets.

Carpet Backings – Polypropylene (ActionBac®), woven, Axminster, Wilton, hot melt, unitary, needle-punch, urethane foam (Enhancer™), polyurethane laminate (LifeSpan®), sponge-rubber, jute, and latex-foam. For backings not listed please contact our Technical Department at (706) 277-5294.

For interior installations only. Do not use this adhesive for vinyl backed products.

Substrates:

Concrete, APA underlayment grade plywood, vinyl composition tile (free of wax), primed gypcrete (refer to ASTM F2419) and terrazzo. Check with the flooring manufacturer for their underlayment recommendations.

Vinyl composition tile must be well bonded and limited to one layer. Carpet should not be adhered to vinyl composition tile in high or heavy traffic areas. Do not install a non-porous backed carpet over vinyl composition tile.

Surface Preparation:

Subfloors must be structurally sound, dry, smooth, level, flat and free of excess moisture/alkali and all substances (oil, wax, grease, oil based sealers, adhesives, etc.) that might interfere with the performance of the flooring or its installation. Ensure the appropriate flatness/smoothness to prevent accelerated wear.

All substrate cracks, holes, high spots and irregularities must be adequately repaired to ensure a smooth, finished appearance to prevent show through and accelerated wear. Patching compounds must be

suitable for the use application, polymer-fortified and applied according to the manufacturer's instructions. Expansion or other moving joints must not be filled or covered with flooring. Refer to ASTM 710 Standard Practice for Preparing Concrete Floors.

Wood – Subflooring, such as APA underlayment grade plywood, hardwood, oriented strand board (lightly sanded), or other materials, must be flooring grade and installed to the manufacturer's specifications with adequate ventilation and moisture protection. Ensure wood substrates have a minimum 18 in. crawl space with adequate ventilation and moisture barrier protection. Cracks, chips and joints must be properly patched or repaired. Existing vinyl composition tile must be limited to one layer and well bonded. Remove all wax, floor finishes, dirt and contaminants that may interfere with the bond.

Refer to CRI Carpet Installation Standard available at www.carpet-rug.org.



FLOORING TYPE	TROWEL SIZE	ITEM #	COVERAGE
Direct Bond Carpet (polypropylene, woven)	1/8 in. x 1/8 in. x 1/16 in.	49737 10137-12	90–110 sq. ft. per gallon
Direct Bond Carpet (closed-celled urethane, Enhancer®)	3/32 in. x 3/32 in. x 3/32 in.	10-820	100–120 sq. ft. per gallon

The trowel notches referenced are those typically recommended for the type of flooring being installed. They are normally the minimum size recommended. Surface conditions (roughness and porosity of substrate), type of flooring and backing will ultimately determine the required trowel notch size and coverage.

Always check with the specific flooring manufacturer's recommendations for their specific trowel requirements. Ensure 100% transfer of adhesive to the substrate and the flooring backing.

General:

Ensure substrate, flooring material and adhesive are fully acclimated prior to installation at the same temperature and humidity level expected during normal use (between 65–95°F / 18–35°C with a relative humidity (RH) of no greater than 65%). Refer to flooring manufacturer’s specific recommendations and industry standards.

Flooring must be installed when the indoor temperature is between 65–95°F (18–35°C) with a maximum RH of 65%, 48 hours before, during and 72 hours afterward. Large temperature or humidity increases or decreases can affect the flooring and performance of the installation.

Ensure adequate ventilation during flooring installation.

Physical Characteristics (70°F, RH 50%):

Open Time: Up to 20 minutes

Working Time: Up to 40 minutes

Shelf Life: One year in unopened container

Product Type: SBR latex

Moisture Vapor Emissions: 10 lbs. or less (ASTM F1869) /

90% or less (ASTM F2170)

pH must not exceed 10

Protect from freezing

Application and Installation:

Spread adhesive uniformly. Allow up to 20 minutes of open time before you place your flooring into the adhesive. Adhesive ridges should be of sufficient height to achieve full coverage of the substrate and the deepest recesses in the back of the flooring material.

Within the 40 minute working time, place flooring into the adhesive while the adhesive is still fresh and transfers readily to the flooring backing. The amount of open time and time in which you have time to place the flooring will vary with temperature and humidity. The higher the temperature and the lower the humidity the faster the adhesive will set.

Lift a corner periodically to see if the adhesive is transferring 100% to the back of the flooring. If the adhesive is not transferring to the backing of the underlayment remove adhesive and reapply.

After Installation – Restrict foot traffic and moving of heavy objects for 24 to 48 hours to allow adhesive to cure properly. Premature traffic can cause installation failure.

Clean Up:

Fresh adhesive – warm soapy water. *Dried adhesive* – use mineral spirits sparingly with a clean, white cotton cloth. **DO NOT POUR CLEANER DIRECTLY ONTO FLOORING.**

Limited Warranty:

15-Year Direct Bond / 7-Year Direct Bond. Roberts warrants that this product will be free from manufacturing defects for 12 months from the date of purchase, when applied in accordance with Roberts’ instructions and industry standards. Roberts’ sole liability is to either supply new product or refund the original purchase price. **This limited warranty excludes all other express warranties including the warranties of merchantability for a particular use or purpose.**

Any implied warranties arising by operation of law are limited to one year. Roberts will not be liable for any incidental or consequential damages. Visit www.robertsconsolidated.com for full warranty details.

Refer to safety data sheet, www.robertsconsolidated.com, industry standards and manufacturer’s guidelines prior to installation for additional information.

For technical assistance please contact our Technical Department at (706) 277-5294.

Available Sizes:

SIZE	PRODUCT #	UPC
4 Gallon	3095-4	075378309543
1 Gallon	3095-1	075378309512



made in
USA

WARNING: EXISTING FLOORING AND ADHESIVES MAY CONTAIN ASBESTOS. Unless you have confirmation that the existing flooring system is not asbestos containing, do not sand, dry sweep, dry scrape, abrade, drill, saw, bead blast, mechanically chip or pulverize existing flooring or adhesive without taking all appropriate precautions. Refer to local, state and federal guidelines for treatment and removal of these products. You may also refer to the Resilient Floor Covering Institute’s “Recommended Work Practices for Removal of Resilient Floor Coverings.”

EXISTING PAINT MAY CONTAIN LEAD. Unless you have confirmation that the existing paint is not lead containing, do not sand, dry sweep, dry scrape, abrade, drill, saw, bead blast, mechanically chip or pulverize existing paint without taking all appropriate precautions. Refer to local, state and federal guidelines for treatment and removal of lead containing paint. You may also refer to www.epa.gov/lead