| Product Specification Patriot Branded Paper | | | | | | |
|---|--------|---------|--------|---|--------|------------------|
| | | | | | | |
| Origin Date: | 1/ | 18/2004 | | | | |
| Revised Date: | 11/ | 16/2009 | | | | |
| | Reject | · | · | | Reject | |
| Property | Min | | Target | | Max | Test Information |
| Basis Weight (#/MSF) | 35.0 | · | 39.0 | · | 42.0 | |
| Caliper (mils) | 10.0 | · | 11.0 | | 13.0 | |
| Moisture (%) | 6.5 | · | 8.0 | | 10.0 | |
| Tear MD | | | | | | |
| Tear CD | | · | · | · | | |
| Cobb (G/100CM2) | | | | | | |

Special Instructions:

Tensile MD
Tensile CD
Ring Crush MD
Ring Crush CD

1.) Furnish: Recycled Fiber

2.) Only use TAPPI test methods.

This product is non-toxic and safe for handling.

Recommended Use In: Floor Protection Paint Protection

Floor Underlayment Cabinet & Window Protection

General Purpose Sheathing Temporary Weed Control

Roofing Drainage Fields

Qualities:

Extra Heavy For Tough Jobs Retail Quality Roll

Tightly Wound Rolls UPC Code For Your Retailer

Stack 4-5 High in Warehouse Consistent Quality

Highest Quality Paper Brown Should Not Bleed, however, always test

Proven Quality in the Field with unique jobs, chemicals used and/or materials