



8mm Rubber Sports Flooring available in Rolls, Square Tiles & Interlocking Tiles

PERFORMANCE CRITERIA

TENSILE STRENGTH	ASTM D412	200 lb/in ² min
FLEXIBILITY ¼" MANDREL	ASTM F 137	PASS ¼-inch mandrel
STATIC LOAD (1000 lb/in ²)	ASTM F 970	LESS THAN 0.020-inches
COEFFICIENT OF FRICTION	ASTM D 2047	>0.9-inches
THERMAL CONDUCTIVITY	ASTM C 518	0.406 BTU-in/hr-ft ² - °F
AMBIENT NOISE REDUCTION	ASTM C 423	0.10 Sabin/ft ²
IMPACT INSULATION CLASS	ASTM E 492	45 Minimum
SOUND TRANSMISSION COEFFICIENT	ASTM 413	45 Minimum
V.O.C. COMPLIANT	ASTM D 5116	YES
BALL REBOUND	EN 12235	PASS
FLOORSCORE	CA Specification 01350	CERTIFIED

CHEMICAL RESISTANCE

Ammonia-Good	Human Sweat-Good	Alkaline Base-Good
Bleach-Good	Alcohol-Good	Petroleum Oils-Good
Disinfectant-Good	Oxidizing Acids (concentrated) –Weak	
Adhesive:	Urethane base recommended	
Line Paint:	Suitable for interior or exterior synthetic rubber	
Storage:	Rolls on side, minimum 55 degrees Fahrenheit, less than	
50% humidity. Sub-flooring:	Should not vary more than 1/8" in ten ft.	
New concrete/asphalt:	30 days cure prior to installation of rubber	
Maintenance:	Under normal usage light mopping: common	
detergents if needed.		
STANDARD ROLL:	4' WIDE BY 25' LONG	
SQUARE TILE:	24" BY 24" 4 SF/Tile	
INTERLOCKING TILE:	23" BY 23" 3.67 SF/Tile	

- Post-Consumer recycled rubber
- LEED benefits
- Lifetime Warranty
- Residential & Commercial applications
- Superior Sound Deadening
- Water Resistant
- Fire Retardant, Code Compliant
- Mold & Mildew resistant
- Lays flat, easy to install
- Thickness: 8mm

Fungus/Mildew: Sports Absorber is non-absorbent so will not support mold and mildew. No harsh chemical treatments are necessary.

CLEANING PROCEDURES

Initial Cleaning

- a. Remove all surface soil, debris, sand, and grit by sweeping, dust mopping, or vacuuming with a high

CFM vacuum. For large areas, use auto scrubbers to clean floors.

1. Scrub floor with a mild cleaner such as Betco 13804, using buffer or auto scrubber with a soft nylon brush or approved pad. Avoid flooding the floor.
2. Pick up solution with a wet vacuum, rinse with clean water and vacuum up the rinse water with a wet vacuum and allow to dry thoroughly (6-8 hours).

Daily/Regular Cleaning

- a. Sweep, dust mop, or vacuum floor to remove surface soil, debris, sand, and grit.
1. Damp mop with a microfiber mop or auto- scrub using an approved pad or nylon brush with a mild cleaner such as Betco 13804.

Restorative Maintenance

- a. Sweep and dry vacuum floor thoroughly.
1. Heavy scrub floor with Sports Flooring Cleaner such as Betco 67004 or a Sports Flooring Stripper such as Betco 18404. This cleaning may be performed with an auto scrubber or rotary scrubber.
 - a. Vacuum soiled solution with a wet/dry vacuum.
 - b. Rinse with clean water.
 - c. Pickup solution with a wet vacuum.
 - d. Allow floor to thoroughly dry.

Heavy Soil

1. Remove as much surface soil, debris, sand, and grit as possible by sweeping, dust mopping, or vacuuming.
2. Scrub floor with Sports Flooring Cleaner such as Betco 67004 or a Sports Flooring Stripper such as Betco 18404, using a buffer or auto scrubber with an approved pad.
3. Pick up solution with a wet vacuum, rinse with clean water and allow to dry thoroughly (6-8 hours).