

# Spectrum Series

3mm Dry-Back Glue Down (Smooth Texture)

## 1. MANUFACTURER

Surface Source USA Inc.  
601 New Jersey Church Rd, Lexington, NC 27292  
P- 888.862.9898  
www.primoflorzusa.com

## 2. PRODUCT DESCRIPTION

Primo Florz Spectrum 3200 is designed for use in commercial and residential applications. The Spectrum 3200 collection features a natural wood look. Its rugged construction, including a 32 mil wear layer topped with Maxim Shield UV cured ceramic finish permits maximum durability ensuring long lasting beauty without the use of a floor finish. The composition ensures 100% VIRGIN materials. With excellent resistance to abrasion, chipping, cracking, and permanent indentations for heavy-duty performance requirements and to help conceal most substrate irregularities, and yet it is flexible for fast and economical installations.

Spectrum 3200 is the perfect choice for residential and commercial applications, or wherever both function and high design are essential. The surface includes a micro bevel smooth surface to enhance the unique look of wood, while adding slip resistance qualities to the plank. Precision cutting allows for easy installation with tight seams.

### Available Sizes (All Dimensions Nominal)

**Gauge:** 1/8" (3 mm)

**Size:** 6" x 48"

**Wear Layer:** 32 mil UV urethane Maxim Shield™

**Packaging:** 18 pieces per carton  
(36 sq. /ft. per carton)

## 3. TECHNICAL DATA

### Product Classification

ASTM F 1700 - Solid Vinyl Tile; Class III, Type B

### Fire Testing Information

ASTM E 648, Critical Radiant Flux - Class 1, > .45 W/cm<sup>2</sup>

### General Performance Information

ASTM C1028-96, Static Coefficient of Friction .060

slip resistance Passes ADA/OSHA standard -

ASTM F 970, Static Load - 2,000 PSI, < .005"

ASTM F925, Resistance to Chemicals - No Change

ASTM F1514, Heat Stability of Color - ΔE < 8 Avg

ASTM F1515, Light Stability of Color - ΔE < 8 Avg

ASTM F1914, Residual Indentation - 3.4%

ASTM F2199, Dimensional Stability -.20" / in ft

ASTM E648 Critical Radiant Flux Class 1

ASTM F2753 Rolling load over Resilient .024 inch

ASTM E648 Fire Test Data (Flame Spread) >0.45 W/cm<sup>2</sup>, Passes

ASTM E662 Fire Test Data (Smoke) <450, Passes

## 4. TECHNICAL ASSISTANCE

Technical service information and assistance may be obtained 1-888-862-9898 or www.primoflorzusa.com

## 5. LIMITED WARRANTY

Limited One (1) Year Manufacturer's Warranty

Limited Twenty (20) Year Commercial Wear Warranty

Limited Forty (40) Year Residential Wear Warranty



NATURAL BAMBOO  
LVP43327G

STONEHEDGE OAK  
LVP43330G

CHARCOAL OAK  
LVP43328G

AMERICAN CHERRY  
LVP43331G

NATURAL HICKORY  
LVP43329-G

PEARL GREY OAK  
LVT43332G