

# ARDEX FG-C™

## MICROTEC® Unsanded Floor & Wall Grout

A high-performance, Portland cement-based, unsanded grout that delivers fuller, more aesthetically pleasing grout joints with an ultra-smooth finish for floor and wall tile joints.

Use for porcelain, glass, quarry, ceramic and mosaic tile, as well as most natural stone tiles. \*

### Key Features

- **High-strength:** for joints up to 1/4" (6 mm), porcelain joints up to 1/8" (3 mm)
- **Excellent color consistency**
- **Stain resistant**
- **Water and frost resistant**
- **For interior and exterior floors, walls and showers**
- **Antimicrobial**
- **Mold and mildew resistant**
- **Available in 35 ARDEX colors**

### Installation

**Packaging:** 25 lb. (11.3 kg) bag / 10 lb. (4.5 kg) box

**Pot life:** 90 minutes

**Working Time:** 90 minutes

**Open to traffic:** 4 hours

**VOC:** 0

### Performance

\*ARDEX FG-C is not suitable for use with moisture-sensitive stone. \*\*For porcelain tiles 1/8" or wider in high-stress areas, use ARDEX FL™ Rapid Set, Flexible Sanded Grout



Refer to the technical data sheet at [www.ardexamericas.com](http://www.ardexamericas.com) or call 888-512-7339 prior to installation. For free ARDEX product training click on ARDEX Academy.

For easy-to use ARDEX Product Calculators and Product Information On the Go, download the ARDEX App at the iTunes Store or Google Play.



ARDEX GROUTS



888-512-7339  
+1-724-203-5000  
[www.ardexamericas.com](http://www.ardexamericas.com)