



ARDEX FLEX CAULK™

Siliconized Acrylic Color Caulk

For use with both ARDEX Sanded™ and ARDEX Unsanded™ Grouts

Color matched to ARDEX Grouts

Stain resistant

Mold & mildew resistant

Stays flexible

Use for interior and exterior installations

**ARDEX Engineered Cements
400 Ardex Park Drive
Aliquippa, PA 15001 USA
Tel: 724-203-5000
Toll Free: 888-512-7339
Fax: 724-203-5001
www.ardexamericas.com**

ARDEX FLEX CAULK™

Siliconized Acrylic Color Caulk

Description

Premium siliconized acrylic color caulk used for caulking and sealing corners, edges and joints created by change-of-plane or change-of-materials in interior and exterior applications. Use ARDEX FLEX CAULK™ for caulking countertops and around sinks, bathtubs and backsplashes, as well as in showers. Use on joints up to 1/2" wide.

Substrate Preparation

The surface or area to receive caulking must be dry, clean and free of dust, dirt, mildew, oil and other foreign substances. Surface temperature must be above 50°F (10°C). Remove any old caulking and clean area with mild solution of bleach and water before applying new caulk. Be sure the area to be caulked is completely dry before applying caulk.

Application

Cut tube nozzle to desired bead thickness. Apply caulking and tool within 10 minutes of application using a wet finger or damp, smooth sponge. Any excess may be cleaned up with a damp cloth before the caulk begins to skin over.

The caulk will be fully cured in 3 to 5 days, depending on temperature, airflow, humidity and thickness of application. In humid or enclosed areas, i.e. enclosed showers, use a room fan to circulate air to assist in curing the caulk.

Clean all tools with soap and water before caulking dries.

Notes

Not for use in permanent submerged areas, such as swimming pools and fountains.

ARDEX FLEX CAULK is not a replacement for a waterproofing membrane. Where waterproofing is needed, please refer to the ARDEX Technical Brochures for ARDEX Waterproofing Compounds.

Technical Data According To ARDEX Quality Standards

All data based on product performance at 70°F (21°C)

Coverage:	Approx. 25 linear ft. at 1/4" x 1/4" joint width. (Coverage will vary depending on joint size and width)
Working Time:	10 minutes
Full Cure:	3 to 5 days at 70°F (21°C)
Shore "A" Hardness (ASTM C661):	25
Tensile Strength:	300 psi
Elongation:	500%
Service Temperature:	-40°F (-40°C) to 350°F (176°C)
Joint Movement:	+/-50%
Skin Time:	5-10 Minutes
Tack-Free Time:	15-30 Minutes
Packaging:	10.3 oz (310 mL)
Storage:	Store in a cool dry place. Protect from freezing. Do not expose to direct sunlight.
Shelf Life:	36 months, if unopened
Warranty:	Please see the ARDEX Tile & Stone Installation System Warranty Brochure

Colors Available

Fresh Lily 02	Coffee Bean 17
Sugar Cookie 03	Dove Gray 18
Antique Ivory 04	Silver Shimmer 19
Floating Driftwood 07	Ocean Gray 20
Vintage Linen 08	Slate Gray 21
Natural Almond 09	Black Licorice 24
Irish Crème 10	Organic Earth 26
Barley 11	Gentle Blush 28
Wild Mushroom 12	Fresh Magnolia 29
Stone Beach 13	Pink Champagne 30
Chocolate Mousse 14	Burnt Orange 31
Gray Dusk 15	Brilliant White 35
Ground Cocoa 16	

This product contains colorants that may stain some porous materials, such as walls, wallpaper, etc. Mask or shield these areas to protect from staining. Test in a non-conspicuous area to see if staining will occur.

© 2018 ARDEX Engineered Cements, L.P. All rights reserved. AT231 (02/18)

Visit www.youtube.com/ARDEX101 to watch ARDEX Americas product videos.

For easy-to-use ARDEX Product Calculators and Product Information On the Go, download the ARDEX App at the iTunes Store or Google Play.



ARDEX Engineered Cements
400 Ardex Park Drive
Aliquippa, PA 15001 USA
Tel: 724-203-5000
Toll Free: 888-512-7339
Fax: 724-203-5001
www.ardexamericas.com