

## COLOR CAULK

Southcrete 800 - 801



SGM Color Caulk is a premium single component sealant that provides a long lasting, water resistant seal. Southcrete® Premium Color Caulk is a high quality tile and fixture caulk that is suitable for both professionals and “Do-It-Yourselfers.” Southcrete® Color Caulk is designed to be used for caulking around ceramic tile, marble, granite and natural stone floors and fixtures, countertops, showers, tubs and sinks to restore cracked or worn grout lines.

### MANUFACTURER:

SGM, Inc.  
1502 SW 2nd Place  
Pompano Beach, FL 33069-3220  
(800) 641-9247  
(954) 943-2288  
Fax: (954) 943-2402  
www.sgm.cc  
sales@sgm.cc

### USES:

- Interior
- Exterior
- Between vertical and horizontal abutments
- Joints between door threshold and tiled entry

### PREPARATION:

Surfaces must be dry and free of dust and debris.

### COVERAGE:

Spread rate on our caulk 10.5 cartridges is as follows:

¼ bead	25 linear feet
3/16 bead	40 linear foot
1/8 bead	50 linear feet

### LIMITATIONS:

Do not apply to surfaces that may go below 40°F (4.5°C) or above 105°F (40.6°C) This product may contain high levels of colorant and may stain some porous materials such as wallpaper, wood or drywall. Masking or shielding of these areas may be necessary.

### PHYSICAL PROPERTIES:

Basic Composition	Silicone based elastomeric acrylic
Appearance	White or pigmented compound smooth or textured
Wt/gal	12.50 lbs
Consistency	Non-Sag
Solids	Approximately 80%
Odor	Mild to low
Open Time	10-20 min

### DIRECTIONS:

1. Surfaces must be dry and free of dust and debris.
2. Cut nozzle tip to desire bead size.
3. Dispense sealant where needed.
4. Smooth if necessary with wet finger.
5. Remove excess sealant with wet finger or damp cloth before dry.
6. Allow 72 hours for curing.
7. A second coat may be necessary. Wait 24 hours before applying a second coat. Do not use below 40°F (4.5°C) or above 105°F (40.6°C) - Not for underwater use.

Store away from extreme heat or cold. Color match is complete when sealant is fully cured. Wet sealant will appear lighter in color.

### SAFETY PRECAUTIONS:

Avoid contact with eyes or skin. Avoid repeated breathing of vapors. Do not

take internally.

### FIRST AID:

**INHALATION / OVEREXPOSURE:** If dizziness or nausea occurs, remove person to fresh air and seek medical attention. **SWALLOWING:** If swallowed, do not induce vomiting, call Poison Control Center, Hospital Emergency Room or Physician immediately. **EYE CONTACT:** Flush eyes immediately and thoroughly with large amounts of clean water for at least 15 minutes. If irritation persists, see a physician. **SKIN CONTACT:** Wash skin thoroughly with room temperature water and mild soap.

### CLEAN UP:

Clean up excess uncured sealant with a damp cloth. Wash hands and tools with soap and water. Dried material must be cut or scraped away.

### CONTAINS:

Calcium Carbonate(CAS#1317-65-3)  
Mineral Spirits (CAS#8052-41-3)  
Propylene Glycol (CAS#57-55-6)  
Titanium Dioxide (CAS#13463-677)  
Acrylic Copolymer (CAS#none)  
(mixture)  
VOC content: 25-50 g/l

### LIMITED WARRANTY:

S.G.M., Inc. will replace any material proved defective with the maximum shelf life on unused material of up to one (1) year. If our products are not

found to conform to our high standards, notify S.G.M., immediately in writing. There is no other obligation expressed or implied, and we assume no liabilities for damages of any kind. Suitability of the product for an intended use shall be solely up to the user.

**TECHNICAL SERVICES:**

Technical assistance, including more detailed information, product literature, test results, project list, samples, assistance in preparing project specifications and arrangements for job site inspection and supervision, is available by contacting SGM Technical Services Department.

(800) 641-9247  
(954) 943-2288  
Fax: (954) 943-2402  
[www.sgm.cc](http://www.sgm.cc)  
[ts@sgm.cc](mailto:ts@sgm.cc)