

HENRY®

The Professional's Formula For Success™



HENRY® 351 FastPro™ Fast Grab, Pro Grade Carpet Adhesive



Professional-grade adhesive for the installation of most commercial and residential carpet.

Use For: Jute, Action Bac® (polypropylene), urethane foam, latex foam (rubber), unitary, unitary Action Bac®, hot melt, woven and urethane laminate backings, as well as non-backed needle-punched carpet. Also for carpet-to-cushion and cushion-to-substrate (permanent) in double glue-down installations.

Key Features & Benefits:

- Versatile - for use with most carpet backings
- Aggressive early grab-reduces edge curl
- Excellent bond integrity - for moderate to heavy traffic areas
- Strong rebond - when re-rolling after installation
- Contributes towards LEED® points

Bonds To:

All grade levels - concrete, well-bonded cementitious underlayments, APA-grade underlayment plywood (untreated), radiant-heated subfloors where temperatures do not exceed 85°F (29.4°C), terrazzo, ceramic tile, marble, certain epoxy coatings and existing, fully adhered, non-cushioned backed resilient.

PLEASE READ FULL TECHNICAL BROCHURE AND SDS BEFORE INSTALLING (WWW.WWHENRY.COM)



Coverage:

Latex- and urethane foam-backed carpets:

V-Notch
3/32"D x 3/32"W x 3/32"A
144-162 ft² / gal. (16-18 m² / L)

Cushion to Substrate (Permanent): Sq. Notch
1/16"D x 1/16"W x 1/16"A
144-162 ft² / gal. (16-18 m² / L)

Carpet to cushion (Double Glue-Down): U-Notch
3/16"D x 1/8"W x 1/8"A
54-72 ft² / gal. (6-8 m² / L)

Other Recommended Carpet Backings: V-Notch
1/8"D x 1/8"W x 1/16"A
90-108 ft² / gal. (10-12 m² / L)

SystemOne™

GREENLINE
ENVIRONMENTAL TECHNOLOGY



HENRY®

The W.W. Henry Company
(888) 512-7339

www.wwhenry.com